

Residential Elevator

Taking your home to the next level

0



(A A A

4

10APR25 | MK-000217-B

Add a touch of luxury to suit your lifestyle

with the latest in premium home access: a Pollock Residential Elevator





Images for guidance only

Travel in style and with ease in your home with our elegant Residential Elevator, and enjoy your home well into the future.





Providing smooth and quiet through-floor travel, the elevator includes external controls on both floors, and is equipped with our **Intelligent Logic Diagnostic Display,** offering a wealth of benefits to the user.





Quick and easy to install, the lift is located close to, but not attached to the wall. When the lift is not in the room, enjoy all of your living space.

UNIQUE TO POLLOCK HOMELIFTS

Intelligent Logic Diagnostic Interface

Literation of the second secon

Lift State Error Message Engineer Code

In car diagnostic display screen (4 line) as standard or upgrade to 7" LCD screen

Since 1983, Pollock Lifts have been Ireland's only Residential Elevator manufacturer and the ultimate choice for adding value to home access using the latest technology.

Our innovative digital control system brings a wealth of benefits not only for end users but also for installers and service technicians with easier installation process, simplified servicing, and reduced fault finding.

From installation to operation, every detail has been designed with you in mind.



Trip Counter tracks number of travel cycles throughout lift lifespan



Lift Fault Memory Log on board system for service engineers



Self-check Safety prior to commissioning for extra safety assurance



Service Due Indicator with overdue notification ensuring regular maintenance



Fault Source Identified enabling simple issues to be fixed over the phone



Lift Deactivation System

Features and options to make it your own

Configurations to suit your lifestyle

Standard Features

Options

Electric Drive System

500 lb (230kg)	-
16 fpm (0.08m/s)	-
74 ¹³∕₁₅" (1900mm)	70 ⁷ / ₈ " (1800mm) or 78 ³ / ₄ " (2000mm)
13 ' 8 3 /4" (4.2m)	Extended travel up to 15' 9" (4.8m)
Transparent	-
Ceiling Fix	Wall Fix
Yes	-
	16 fpm (0.08m/s) 74 ¹³ /16" (1900mm) 13' 8 ³ /4" (4.2m) Transparent Ceiling Fix

Cabin Features

Lift Color	RAL 7035	Custom Color	
PC Wall Panels (Compact/Twin)	³∕16" (4mm)		
PC Wall Panels (Large)	³∕₅" (10mm)		
Rear Wall Side Panels	RAL 7042	Custom Color	
Flooring	Grey Anti-slip Vinyl	Marble or Oak effect vinyl, or Custom	
LED Lighting	White	Color Changing Mood Lighting	
Door Handrail	Yes	-	
Cabin Handrail	Yes, with control buttons	_	
Tip-up Seat	No	265 lb (120kg) Tip-up Seat	

Operation

Controls	Remote (radio)	Surface or Flush (wired)
Diagnostic Display	4 Line LCD	7" Color LCD
Door Operation	Manual Powered	
Emergency Telephone	Yes	-
Alarm	Yes	_

Choose the size option that works for you

Available in 3 sizes and 3 cabin heights, you can choose the configuration that best suits your requirements and room dimensions.

The Residential Elevator can be installed in any room, according to your desired travel within your home and room floor plans.





Cabin Heights 70 ⁷/₈", 74 ¹³/₁₆", 78 ³/₄"

Control the lighting to suit your mood

Why only have white LED lighting when you can enjoy a full spectrum of lighting colors?

Select the optional color-changing LED lighting with remote control.







Enjoy the benefits of a Electric Drive System

Our Residential Elevator uses Electric Drive as standard to provide the most comfortable travel experience and installation and operational benefits.





- Soft start/stop
- Quieter travel
- Self-contained unit
- Smaller footprint
- Higher travel distance
- Less expensive to run
- Environmentally friendly



In-car emergency telephone



Shallow ramp – less than 1"

"

We love our Residential Elevator. Quiet and stylish - we were able to choose colors that perfectly matched our decor and the service from Pollock Homelifts was outstanding.

Footprint Options

	Electric Drive System		
Application	Private Residential Use Only		
Lift/Trapdoor Safe Working Load	500 lb (230kg)		
Maximum Travel	13' 9 ³∕₅" (4.2m)		
Optional Extended Travel	up to 15' 9" (4.8m)		
Rated Speed	16 fpm (0.08m/s)		
Noise db (1m / 5m)	55 / 50		
Power Supply/Motor	115v (20a breaker)/0.75kW		
Duty Cycle	10 cycles/hour		
Operating Temperature Range	50°F to 104°F (10°C to 40°C)		
Safety Features	Constant Pressure, Bottom Tray and Trapdoor Sensor, Battery Lowering, Telephone, Overspeed Brake		
Lifting Mechansim	Rope suspension system		
Design & Manufacturing Standard	ETL Approved to ASME 17.1 and 17.5, and CSA B44.1		

A = Product Width
B = Product Length
C = Usable Width
D = Usable Length

- E = Min. upper ceiling height
- F = Max. aperture depth
- G = Min. travel
- H = Min. lower ceiling height

Lift Footprint (Usable C x D)	А	В
21 ⁵/₁₆" x 29 ¹/₂" (SM)	31 ¹∕₅"	63 ³⁄4"
(542mm x 750mm)	(790mm)	(1620mm)
33 ⁷ / ₁₆ " x 29 ¹ / ₂ " (MD)	43 ½"	75 7⁄8"
(850mm x 750mm)	(1098mm)	(1928mm)
33 ⁷/16" x 49 ³/16" (LG)	43 ½"	95 ⁹⁄16"
(850mm x 1250mm)	(1098mm)	(2428mm)

Lift Height	Е	F (max)	G (min)	G (Strd)	H (min)
1.8m Shrt cabin	89 ¹⁵⁄16"	17 ¹¹⁄16"	78 ³⁄4"	165 ³∕₅"	72 ¹³⁄16"
	(2285mm)	(450mm)	(2000mm)	(4200mm)	(1850mm)
1.9m Strd cabin	93 7⁄8"	17 ¹¹⁄16"	82 ¹¹⁄16"	165 ³∕₅"	76 ³⁄4"
	(2385mm)	(450mm)	(2100mm)	(4200mm)	(1950mm)
2.0m Tall cabin	97 ¹³⁄16"	17 ¹¹⁄16"	86 ⁵∕₅"	165 ³⁄₅"	80 ¹¹⁄16"
	(2485mm)	(450mm)	(2200mm)	(4200mm)	(2050mm)







NOTES

Manufactured to the highest safety standards

All our lifts are compliant with international standards and quality requirements.





Machin





Intertek ETL Approved to ASME 17.1 and 17.5, and CSA B44.1





Email: pollock@harmar.com Phone: 833-364-8700 www.pollock-residentialelevators.com



1500 Independence Blvd., Suite 220 Sarasota, FL 34234 800-833-0478